



## Graphite with Inconel Filaments Braided Packing Style 1106



### Construction

Packing made of an expanded graphite yarn of industrial quality, impregnated with a graphite-based mix and reinforced with Inconel Filaments., The products are almost suitable to all media, such as hot water, steam, acids, alkalis, organic solvents, hydrocarbons, low temperature liquids, ect. The

sealing capability is more better and safety. It is the most effective composite parts for solving problems.

### Technical Data:

Maximum Temperature	:	650 °C Steam
		450 °C Oxidizing Condition
Minimum Temperature	:	-204 °C Cryogenics
Maximum Pressure	:	350 bar
Velocity	:	N/A
Chemical Resistant (pH)	:	0 – 14
Application	:	Valve

#### WARNING:

Properties/applications shown throughout this brochure are typical. Your specific application should not be undertaken without independent study and evaluation for suitability. For specific application recommendations consult Khuner. Failure to select the proper sealing products could result in property damage and/or serious personal injury. Performance data published in this brochure has been developed from field testing, customer field reports and/or in-house testing. While the utmost care has been used in compiling this brochure, we assume no responsibility for errors. Specifications subject to change without notice. This edition cancels all previous issues. Subject to change without notice.

Khuner is a registered trademark for packing, seals, gaskets, and other products of Khuner.