

Pure Expanded PTFE Joint Sealant



Khuner Pure Expanded PTFE Joint Sealant is made of Top premium grade 100% pure expanded P.T.F.E. supplied in roll with one adhesive face for ease of installation. It is easily compressible and seals any kind of irregular, damaged or defective surface in a safe way.

Technical Data Sheet

Composition	: Top Premium Grade 100% Pure Expanded P.T.F.E.
Color	: White
Temperature Range (°C)	: - 200 °C to + 270 °C
Max. Pressure (bar)	: 140 bar
pH	: 0 - 14
Compression Set, ASTM Method B (%)	: 25 - 50 %
Elongation, min., (%)	: 500 %
Tensile Strength, min., ASTM D412, (N/mm²)	: 25 N/mm²
Thickness available	: 2.0, 3.0, 4.0, 5.0, 6.0, 7.0, 9.0, 10.0

WARNING:

Properties/applications shown throughout this brochure are typical. Your specific application should not be undertaken without independent study and evaluation for suitability. For specific application recommendations consult Khuner. Failure to select the proper sealing products could result in property damage and/or serious personal injury. Performance data published in this brochure has been developed from field testing, customer field reports and/or in-house testing. While the utmost care has been used in compiling this brochure, we assume no responsibility for errors. Specifications subject to change without notice. This edition cancels all previous issues. Subject to change without notice.

Khuner is a registered trademark for packing, seals, gaskets, and other products of Khuner.