

Carbon Fiber with PTFE Dipped Braided Packing Style 1203



Carbon Fiber with PTFE Dipped Braided Packing Style 1203 is manufactured with High Quality Carbon Fiber Filaments lubricated with PTFE. This packing non-contaminate, low abrasion and high chemical resistance for long service. Ideal where contamination is prohibited, as in pulp and paper industry.

Technical Data:

Maximum Temperature	:	340 °C
Minimum Temperature	:	-200 °C Cryogenics
Maximum Pressure	:	50 bar (Rotary/Centrifuge)
Compressibility	:	25 – 50 %
Recovery	:	> 40 %
Maximum Velocity	:	20 m/s
Chemical Resistant (pH)	:	0 – 14
Application	:	All Pumps and Valves

WARNING:

Properties/applications shown throughout this brochure are typical. Your specific application should not be undertaken without independent study and evaluation for suitability. For specific application recommendations consult Khuner. Failure to select the proper sealing products could result in property damage and/or serious personal injury. Performance data published in this brochure has been developed from field testing, customer field reports and/or in-house testing. While the utmost care has been used in compiling this brochure, we assume no responsibility for errors. Specifications subject to change without notice. This edition cancels all previous issues. Subject to change without notice. Khuner is a registered trademark for packing, seals, gaskets, and other products of Khuner.