



Neoprene reinforced fabric rubber sheet Style 6947



Neoprene reinforced fabric rubber sheet Style 6947 is premium grade neoprene, 60 to 85 duro, generally resistance to water, refrigerants, oils and fuels

Technical Data Sheet

Type	: Neoprene
Color	: Black
Temperature Range (°C)	: - 29 °C to + 121 °C
Max. Pressure (bar)	: 17 bar
P x T max. (bar x °C)	: 800 bar x °C
Compression Set, ASTM Method B (%)	: 35 %
Elongation, min., (%)	: 350 %
Tensile Strength, min.,	: 14 N/mm²
ASTM D412, (N/mm²)	
Hardness (Shore A)	: 60 to 85 ± 5 Shore A
Thickness available	: 0.5, 0.8, 1, 1.5, 2, 3, 5, 6, 8, 10 mm.

WARNING:

Properties/applications shown throughout this brochure are typical. Your specific application should not be undertaken without independent study and evaluation for suitability. For specific application recommendations consult Khuner. Failure to select the proper sealing products could result in property damage and/or serious personal injury. Performance data published in this brochure has been developed from field testing, customer field reports and/or in-house testing. While the utmost care has been used in compiling this brochure, we assume no responsibility for errors. Specifications subject to change without notice. This edition cancels all previous issues. Subject to change without notice. Khuner is a registered trademark for packing, seals, gaskets, and other products of Khuner.