



White Silicone Rubber Sheet Style 8950



White Silicone Rubber Sheet Style 8950 is special grade silicone, 60 duro, Generally resistant to moderate or oxidizing chemicals, ozone, concentrate sodium hydroxide. ESA, ISO 9001 and FDA Certificates

Technical Data Sheet

Type	: Silicone
Color	: White
Temperature Range (°C)	: - 100 °C to + 450 °C
Max. Pressure (bar)	: 20 bar
P x T max. (bar x °C)	: 1300 bar x °C
Compression Set, ASTM Method B (%)	: 25 - 40 %
Elongation, min., (%)	: 250 - 400 %
Tensile Strength, min., ASTM D412, (N/mm²)	: 900 psi
Hardness (Shore A)	: 60 Shore A
Thickness available	: 0.5, 0.8, 1, 1.5, 2, 3, 5, 6, 8, 10 mm.

WARNING:

Properties/applications shown throughout this brochure are typical. Your specific application should not be undertaken without independent study and evaluation for suitability. For specific application recommendations consult Khuner. Failure to select the proper sealing products could result in property damage and/or serious personal injury. Performance data published in this brochure has been developed from field testing, customer field reports and/or in-house testing. While the utmost care has been used in compiling this brochure, we assume no responsibility for errors. Specifications subject to change without notice. This edition cancels all previous issues. Subject to change without notice.

Khuner is a registered trademark for packing, seals, gaskets, and other products of Khuner.